

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
10 March 2005 (10.03.2005)

PCT

(10) International Publication Number  
WO 2005/021097 A1

(51) International Patent Classification<sup>7</sup>: A62C 3/00,  
35/00, 35/58, 37/48, F24F 3/16, 13/02, 7/00

Göran [FI/FI]; Ilmari Kiannon kuja 3, FI-04310 TU-  
USULA (FI). METZGER, Harry [FI/FI]; Aleksis Kiven  
tie 49, FI-04200 KERAVA (FI).

(21) International Application Number:  
PCT/FI2004/000512

(74) Agent: HEINÄNEN OY; Annankatu 31-33 C, FI-00100  
HELSINKI (FI).

(22) International Filing Date:  
3 September 2004 (03.09.2004)

(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:  
20031246 3 September 2003 (03.09.2003) FI

(71) Applicant (for all designated States except US): MARI-  
OFF CORPORATION OY [FI/FI]; Virmatie 3, FI-01300  
VANTAA (FI).


(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,  
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

(72) Inventors; and

(75) Inventors/Applicants (for US only): SUNDHOLM,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR REDUCING THE DETRIMENTAL EFFECTS OF A FIRE



(57) Abstract: A method for reducing the adverse effects of a fire, in which method smoke and combustion gases are removed from a space by spraying through at least one first spray head (2) a mist of a medium into a duct part (1) leading away from the space so as to generate a suction from the space into the duct near the orifice (4) of the duct (1). In a first step, the first spray head (2) is activated and, when necessary, a connection is opened from the space into the duct part (1) via the orifice (4) of the duct part by opening a shutter element (5) and, in a second step, the connection from the space into the duct part (1) is closed by means of the shutter element (5) at least when the temperature of the combustion gases and/or smoke exceeds a predetermined value in the duct part or in its vicinity and, when necessary, the spraying through the first spray head (2) in the duct part (1) is stopped.

WO 2005/021097 A1



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*